

### Właściwości

|                     |                             |
|---------------------|-----------------------------|
| Zakres stosowania   | do węży ssących i zwrotnych |
| Typ konstrukcji     | opaska przegubowa           |
| Norma               | podobne do DIN 3017         |
| Materiał            | stal                        |
| Ochrona powierzchni | galwanizowany               |



### Artykuł

| Oznaczenie  | Zakres mocowania (mm) | Szerokość taśmy (mm) |
|-------------|-----------------------|----------------------|
| MRS 17-19   | 17 - 19               | 18,0                 |
| MRS 20-22   | 20 - 22               | 18,0                 |
| MRS 21-23   | 21 - 23               | 18,0                 |
| MRS 23-25   | 23 - 25               | 18,0                 |
| MRS 25-27   | 25 - 27               | 18,0                 |
| MRS 26-28   | 26 - 28               | 18,0                 |
| MRS 29-31   | 29 - 31               | 18,0                 |
| MRS 32-35   | 32 - 35               | 20,0                 |
| MRS 36-39   | 36 - 39               | 20,0                 |
| MRS 40-43   | 40 - 43               | 20,0                 |
| MRS 44-47   | 44 - 47               | 22,0                 |
| MRS 48-51   | 48 - 51               | 20,0                 |
| MRS 52-55   | 52 - 55               | 22,0                 |
| MRS 56-59   | 56 - 59               | 20,0                 |
| MRS 60-63   | 60 - 63               | 20,0                 |
| MRS 64-67   | 64 - 67               | 22,0                 |
| MRS 68-73   | 68 - 73               | 24,0                 |
| MRS 74-79   | 74 - 79               | 24,0                 |
| MRS 80-85   | 80 - 85               | 24,0                 |
| MRS 86-91   | 86 - 91               | 24,0                 |
| MRS 92-97   | 92 - 97               | 24,0                 |
| MRS 98-103  | 98 - 103              | 24,0                 |
| MRS 104-112 | 104 - 112             | 24,0                 |
| MRS 113-121 | 113 - 121             | 24,0                 |
| MRS 122-130 | 122 - 130             | 25,0                 |
| MRS 131-139 | 131 - 139             | 25,0                 |
| MRS 140-148 | 140 - 148             | 25,0                 |
| MRS 149-161 | 149 - 161             | 25,0                 |
| MRS 162-174 | 162 - 174             | 25,0                 |
| MRS 175-187 | 175 - 187             | 25,0                 |
| MRS 188-200 | 188 - 200             | 25,0                 |
| MRS 201-213 | 201 - 213             | 25,0                 |
| MRS 214-226 | 214 - 226             | 25,0                 |
| MRS 227-239 | 227 - 239             | 25,0                 |
| MRS 240-252 | 240 - 252             | 25,0                 |
| MRS 253-265 | 253 - 265             | 30,0                 |
| MRS 266-278 | 266 - 278             | 30,0                 |
| MRS 279-291 | 279 - 291             | 30,0                 |
| MRS 292-304 | 292 - 304             | 30,0                 |

### Warianty produktu

|      |                                           |
|------|-------------------------------------------|
| MRSS | Opaska przegubowa, stal szlachetna 1.4301 |
|------|-------------------------------------------|